



# 17AX4-GT through 17DQ6-B

**17AX4-GT**  
**17D4**  
**17DQ6-A**  
**17DQ6-B**  
ET-T1273C  
Page 1  
11-59

---

---

## DESCRIPTION AND RATING

---

---

**17AX4-GT Diode.** Identical to the 6AX4-GT except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 6AX4-GT Description and Rating sheet for complete data.

**17D4 Diode.** Identical to the 6DA4 except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 6DA4 Description and Rating sheet for complete data.

**17DQ6-A Beam Pentode.** Identical to the 6DQ6-A except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 6DQ6-A Description and Rating sheet for complete data.

**17DQ6-B Beam Pentode.** Identical to the 6DQ6-B except for the following ratings:

Heater Voltage AC or DC .....	16.8 Volts
Heater Current .....	0.45 ± 6% Amperes
Heater Warm-up Time* .....	11 Seconds

\* The time required for the voltage across the heater to reach 80 percent of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the rated heater voltage divided by the rated heater current.

