

VALVE ELECTRONIC

CV1875

MINISTRY OF SUPPLY (D.L.R.D.(A)/R.A.E.

Specification MAP/CV1875 Issue 2 Dated 14.2.52 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

→ Indicates a change

<u>TYPE OF VALVE</u> - Dummy Load Lamp		<u>MARKING</u> See K1001/4	
<u>ENVELOPE</u> - Glass		<u>BASE</u> B4	
<u>RATING</u> Resistance (ohms) 43 Max. Power (W) 200		<u>CONNECTIONS</u>	
		Pin	Electrode
Note		1	No connection
		2	No connection
		3	Filament
		4	Filament
		<u>DIMENSIONS</u> (mm) See K1001/AI/D1 Dimension A (max.) 150 Dimension B (max.) 80	
<u>NOTE</u> A. The lamp shall be suitable for use up to 20 Mc/s			
<u>TEST</u> To be performed in addition to those applicable in K1001			
<u>Test Conditions</u>	<u>Test</u>	<u>Limits</u> Min. Max.	<u>No. Tested</u>
Lamp to be run for 2 minutes (min), with an applied voltage of 93 V.min, 100 V. max., A.C, RMS. Frequency = 50 c/s	Resistance (ohms)	38.7 47.3	100%

CV1875/2/1