

Specification TRE/CV2210 Issue 2 Dated 31.1.52 To be read in conjunction with K1001, ignoring clause 5.2	<u>SECURITY</u> Specification UNCLASSIFIED	Valve UNCLASSIFIED
--	---	--------------------

→ Indicates a change

<b>TYPE OF VALVE</b> - Gas-filled Triode Thyatron			<b>MARKING</b>	
CATHODE - Directly heated			See K1001/4	
ENVELOPE - Glass			<b>BASE</b>	
PROTOTYPE - 5544			B4D	
<b>RATINGS</b>			<b>NOTES</b>	
Filament Voltage	(V)	2.5	A	<b>CONNECTIONS</b>
Filament Current	(A)	12		Pin Electrode
Max. Peak Forward Anode Voltage	(kV)	1.5		1 Grid
Max. Peak Inverse Anode Voltage	(kV)	1.5		2 Filament
Max. Peak Anode Current	(A)	40		3 Filament
Max. Mean Anode Current	(A)	3.2		4 No connection
Max. Surge Anode Current for 0.1 sec. max.	(A)	500	C	TC Anode
Max. Grid Voltage before conduction	(V)	-250	D	<b>TOP CAP</b>
Max. Grid Voltage during conduction	(V)	-10		See K1001/A1/D5.5
Max. Peak Grid Current with anode negative	(mA)	25		
Max. Mean Grid Current with anode positive	(A)	0.2	E	<b>MOUNTING POSITION</b>
Max. Commutation Factor		130	F	Any, between horizontal and vertical with base downwards.
Ambient Temperature Range	(°C)	-55 to +70		
Max. Series Grid Resistor	(Megohm)	0.1		<b>DIMENSIONS (mm)</b>
				See K1001/A1/D1
				Dimension Min. Max.
			A	170 195
			B	- 67
<b>NOTES</b>				
A. Min. Filament Heating Time = 60 secs. B. Max. Time of Averaging = 15 secs. C. This figure is given as a guide to circuit designers for worst fault conditions. D. With anode more negative than -10V. E. Averaged over 1 cycle. F. Commutation Factor is defined as the product of the rate of change of anode current just prior to extinction (in Amp/μsec) and the rate of rise of inverse anode voltage immediately following current extinction (Volt/μsec). If the max. commutation factor is exceeded the life of the valve will be reduced.				

TESTS

CV2210

To be performed in addition to those applicable in K1001.

Test	Test Conditions						Test	Limits		No. Tested	Note							
	V <sub>A</sub> (V)	V <sub>A</sub> peak (V)	V <sub>A</sub> PIV (V)	V <sub>A</sub> Grid (ohms)	V <sub>A</sub> Anode (ohms)	V <sub>G</sub> (V)	I <sub>A</sub> (A)	Min.	Max.									
a 2.5	-	-	-	-	-	-	-	I <sub>A</sub>	(A)	10	14	100% or 8	1					
b 2.5	1500 DC	-	0	Any value 1K-100K ohms	Adjust	-	-V <sub>G</sub> for conductance	(V)	4	15	100%							
c 2.5	1500 DC	-	1M	Any value 1K-100K ohms	Adjust	-	Variation in -V <sub>G</sub> from value found in Test (b)	(V)		2	100%							
d 2.5	Adjust DC	-	0	Any value 1K-100K ohms	0	-	V <sub>A</sub> for conductance	(V)	-	200	100%							
e 2.5	Adjust DC	-	0	0	0	3.2	Voltage drop across valve	(V)		12	100%							
f 2.5	1500 peak AC 50 c/s			0		3.2					100%	2						
(1)	With grid resistor = 1.1 Megohms adjust V <sub>G</sub> to cut-off.						V <sub>G</sub>	(V)	(a) Note value									
	(2) Change grid resistor to 100K ohms and re-adjust V <sub>G</sub> for cut-off.						V <sub>G</sub>	(V)	(b) Note value									
g	I <sub>A</sub> peak = 500A, derived from 50 c/s AC source for period of 0.1 sec. The valve shall be run then for five minutes with I <sub>A</sub> = 3.2A derived from 50 c/s AC source.						Reverse Ig (mA) (Calculated from $\frac{b - a}{1 \text{ Megohm}}$ )		5									
	At the conclusion of this test the valve shall meet all the other electrical require- ments of this specification.								TA									
<u>NOTE</u>																		
<ol style="list-style-type: none"> <li>1. Pre-heat for 3 minutes.</li> <li>2. The grid voltage for this test shall be in the form of a short duration pulse super-imposed on a steady negative bias and arranged such that the valve fires at the 90° point on the anode voltage sine curve. A "heater" circuit may be used so that the current is drawn from a lower voltage supply while 1500V is maintained in the reverse direction, but such a circuit must be approved.</li> </ol>																		

CV2210/2/2