

Specification MOS(A)/CV4049 Issue 2 Dated 6.11.56 To be read in conjunction with K1001 BS448 & BS1409	<u>SECURITY</u>	
	<u>Specification</u>	<u>Valve</u>
	UNCLASSIFIED	UNCLASSIFIED

→ Indicates a change

TYPE OF VALVE - Reliable Double Diode with flexible leads CATHODE - Indirectly-heated (Separate cathodes) ENVELOPE - Glass PROTOTYPE - CV283 EQUIVALENT PINNED VALVE - CV4007	<u>MARKING</u>		
	See K1001/4.		
	<u>BASE</u>		
	B7G/F		
	<u>DIMENSIONS</u>		
	See K1001/AL/D11		
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4007, Issue 3, Dated Dated 21.9.56	Dimensions (mm)	Min	Max
	A. Seated height	-	38
	B. Diameter	16	19
	D. Lead length	38	-
	<u>MOUNTING POSITION</u>		
	Any		

TESTS

The tests required by Specification MOS/CV4007, Issue 3, Dated 21.9.56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Synbol	Limits	Units
	<u>GROUP D</u>						
	DELETE -						
7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			