

B9A Base
Current Equipment Type

TYPE EL84 MINIATURE OUTPUT PENTODE



The BRIMAR type EL84 is a miniature indirectly heated high slope output pentode. The heater is intended for operation in parallel with other valves in A.C. operated or mobile equipment. The valve is primarily designed as an audio output stage in receivers or amplifiers, either singly or in push-pull.

Heater Voltage 6.3 volts
 Heater Current 0.76 amp.

RATINGS

Anode Voltage	300 volts max.
Anode Dissipation	12 watts max.
Screen Voltage	300 volts max.
Screen Dissipation (Zero Signal)	2 watts max.
Screen Dissipation (Max. Signal)	4 watts max.
Cathode Current	65 mA max.

OPERATING CHARACTERISTICS

	Single Valve Class A		Push Pull Class AB1 (2 Valves)		
Anode Voltage	200	250	300		volts
Anode Current (Zero Signal)	50	48	80		mA
Anode Current (Max. Signal)	—	—	92.5		mA
Screen Voltage	200	250	300		volts
Screen Current (Zero Signal)	5.65	5.5	8.5		mA
Screen Current (Max. Signal)	—	—	20		mA
Control Grid Voltage	— 4.6	— 7.3	— 10.4		volts
Cathode Bias Resistor	82	140	130		ohms
Anode Impedance	—	38	—		k Ω
Mutual Conductance	—	11.3	—		mA/V
Optimum Load	4	5.2	8		k Ω
Power Output	3.3	5.7	17		watts
Harmonic Distortion	6.5	10	3.18		per cent.

**OPERATION AS A TRIODE (Anode and Screen Strapped)
CLASS AB1 PUSH PULL (2 Valves)**

Anode Voltage	250	300	volts
Anode Current (Zero Signal)	41	49	mA
Anode Current (Max. Signal)	45	54	mA
Cathode Bias Resistor	270	270	ohms
Optimum Load (anode to anode)	10	10	k Ω
Power Output	3.4	5.2	watts
Total Distortion	1.8	2.0	per cent.

INTER-ELECTRODE CAPACITANCES*

Input	11.0 pF
Output	6.0 pF
Anode to Control Grid	0.5 pF max.
Heater to Control Grid	0.25 pF max.

* With no external shield.

