

## Sharp-Cutoff Twin Pentode With Common Cathode, Grid No.1, and Grid No.2

The 3GS8 is the same as the 4GS8/4BU8 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	$I_h$	$0.600 \pm 0.040$	A
Voltage (AC or DC) at 0.600 A . . . . .	$E_h$	3.15	V

# 3HM5/3HA5

## High-Mu Triode

The 3HM5/3HA5 is the same as the 6HM5/6HA5 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	$I_h$	$0.450 \pm 0.030$	A
Voltage (AC or DC) at 0.450 A . . . . .	$E_h$	2.7	V
Warm-up time (Average). . . . .		11	s

# 3HS8

## Sharp-Cutoff Twin Pentode

The 3HS8 is the same as the 6HS8 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	$I_h$	$0.600 \pm 0.040$	A
Voltage (AC or DC) at 0.600 A . . . . .	$E_h$	3.15	V
Warm-up time (Average). . . . .		11	s



# 3JC6, 3JC6A

## Sharp-Cutoff Pentodes

The 3JC6 and 3JC6A are the same as the 6JC6 and 6JC6A, respectively, except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	$I_h$	$0.600 \pm 0.040$	A
Voltage (AC or DC) at 0.600 A . . . . .	$E_h$	3.5	V
Warm-up time (Average). . . . .		11	s

# 3JD6

## Sharp-Cutoff Pentode

The 3JD6 is the same as the 6JD6 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	$I_h$	$0.600 \pm 0.040$	A
Voltage (AC or DC) at 0.600 A . . . . .	$E_h$	3.5	V
Warm-up time (Average). . . . .		11	s

# 3KT6

## Semiremote-Cutoff Pentode

The 3KT6 is the same as the 6KT6 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	$I_h$	$0.600 \pm 0.040$	A
Voltage (AC or DC) at 0.600 A . . . . .	$E_h$	3.5	V
Warm-up time (Average). . . . .		11	s

