

High-Mu Triode

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (<i>Design-Maximum Values</i>):		
Voltage (AC or DC)	6.3 ± 0.6	volts
Current at heater volts = 6.3	0.180	amp
Peak heater-cathode voltage:		
Heater negative with respect to cathode	100 max.	volts
Heater positive with respect to cathode	100 max.	volts
Direct Interelectrode Capacitances (Approx.): ^a		
Grid to plate	0.52	μf
Grid to cathode, internal shield, and heater.	5.0	μf
Plate to cathode, internal shield, and heater.	3.5	μf
Heater to cathode	2.5 ^b	μf


Characteristics, Class A₁ Amplifier:

Plate Voltage	135	volts
Grid Voltage	-1.2	volts
Amplification Factor	74	
Plate Resistance (Approx.)	6300	ohms
Transconductance	12000	μmhos
Plate Current	8.9	ma
Grid Voltage (Approx.) for plate $\mu_a = 100$	-4.5	volts

Mechanical:

Operating Position	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length	2-1/8"
Maximum Seated Length	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip)	1-1/2" ± 3/32"
Diameter	0.650" to 0.750"
Dimensional Outline	See <i>General Section</i>
Bulb	T5-1/2
Base	Small-Button Miniature 7-Pin (JEDEC No. E7-1)
Basing Designation for BOTTOM VIEW	7FP

Pin 1 - Cathode
Pin 2 - Grid
Pin 3 - Heater
Pin 4 - Heater



Pin 5 - Plate
Pin 6 - Internal
Shield
Pin 7 - Cathode



6FQ5A

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE.	200 max.	volts
GRID VOLTAGE:		
Negative-bias value.	50 max.	volts
CATHODE CURRENT.	22 max.	ma
PLATE DISSIPATION.	2.5 max.	watts

Maximum Circuit Values:

Grid-Circuit Resistance:

For cathode-bias operation 1 max. megohm

^a With external shield JEDEC No.316 connected to cathode except as noted.

^b With external shield JEDEC No.316 connected to ground.

CURVES

shown under Type 6GK5 also apply to the 6FQ5A

